

Specify Part Number

DCN-CON

DCN-NG Concentus Basic

The DCN-CON is the standard delegate conference unit. It is low susceptible for mobile phones, enabling delegates to speak, register a request-to speak, register a response request, listen to the speaker and vote. The flat panel loudspeaker offers superior acoustics with minimal feedback, thus increasing intelligibility.

Features

- Low susceptible for mobile phones
- Compact, attractive delegate unit
- Built-in fold-away flat-panel loudspeaker
- Five voting buttons
- Cable connections located underneath the unit
- External present and fraud contact



Specifications

	Socket for pluggable condenser microphone (ordered separately) with built-in pop and windshield, complete with light ring which illuminates when the microphone is on or when a request to speak has been issued
	Built-in fold-away flat-panel loudspeaker, automatically muted if a microphone is on
	Microphone 'on/off' or 'request-to-speak' button
Controls and indicators	Two 'Microphone on' indicators. One is located above the microphone on/off button (tri color LED for 'request-to speak' 'microphone on' and indication). The other is located on top of the loudspeaker
	'Request-to-speak' confirmation indicator (green LED)
	'VIP' confirmation indicator (yellow LED) 'VIP' LED is lit when the delegate unit is part of the notebook, which is available when PC control software is used.
	Five voting buttons with yellow LED confirmation indicators
	'De-init' switch on the underside of the unit
Interconnection	6.5 ft. (2 m) cable terminated in a molded six-pole circular connector
	Six-pole circular connector for loop-through connections
	Eight-pole modular jack connector for Intercom Handset LBB 3555/00 and external present and Fraude contact e.g., a fingerprint reader
Technical characteristics	Mounting Tabletop (portable or fixed mounting) and flush mounting
	Dimensions (H x W x D) Table top: 2.0 x 10.8 x 6.1 in. (50 x 275 x 155 mm) Flush mounted: 1.2 x 10.8 x 6.1 in. (30 x 275 x 155 mm)
	Weight Approx. 3.1 lbs. (1.4 kg)
	Color Charcoal base with silver panel

Listen Technologies Corporation

8535 South 700 West, Suite A
 Sandy, UT 84070-2515 U.S.A.
 Phone: 1.801.233.8992 or 1.800.330.0891
 Fax: 1.801.233.8995
 Email: info@ListenTech.com

Don't miss a single sound.



Specify Part Number

DCN-CONCS

DCN-NG Concentus Unit with Channel Selector

The DCN-CONCS is similar to the DCN-CON Standard Delegate Unit, but includes a built-in language channel selector. This makes it suitable for conferences where more than one language is used and simultaneous interpretations are available.

Features

- Low susceptible for mobile phones
- Compact, attractive delegate unit
- Built-in fold-away flat-panel loudspeaker
- Five voting buttons
- Cable connections located underneath the unit
- External present and fraud contact



Specifications

	Socket for pluggable condenser microphone (ordered separately) with built-in pop and windshield, complete with light ring which illuminates when the microphone is on or when a request to speak has been issued	
	Built-in fold-away flat-panel loudspeaker, automatically muted if a microphone is on	
	Microphone 'on/off' or 'request-to-speak' button	
Controls and indicators	Two 'Microphone on' indicators	
	Two 'Microphone on' indicator	
	'Request-to-speak' confirmation indicator (green LED)	
	'VIP' confirmation indicator (yellow LED) 'VIP' LED is lit when the delegate unit is part of the notebook, which is available when PC control software is used	
	Five voting buttons with yellow LED confirmation indicators	
	'De-init' switch on the underside of the unit	
Interconnection	6.5 ft. (2 m) cable terminated in a molded six-pole circular connector	
	Six-pole circular connector for loop-through connections	
	Eight-pole modular jack connector for Intercom Handset LBB 3555/00 and external present and Fraude contact e.g., a fingerprint reader	
	Left and right headphones sockets (3.5 mm (0.14 in) stereo jack type) Connection for external microphone or headset microphone (3.5 mm (0.14 in) stereo jack type)	
Technical characteristics	Mounting	Tabletop (portable or fixed mounting) and flush mounting
	Dimensions (H x W x D)	Table top: 2.0 x 10.8 x 6.1 in. (50 x 275 x 155 mm) Flush mounted: 1.2 x 10.8 x 6.1 in. (30 x 275 x 155 mm)
	Weight	Approx. 3.1 lbs. (1.4 kg)
	Color	Charcoal base with silver panel

Specify Part Number

DCN-CONFF

DCN-NG Concentus Full Function

This top-of-the-range, multi-functional delegate unit, which is low susceptible for mobile phones, meets the demands of even the largest conferences. It provides facilities for speaking,

registering a request to speak, registering a request to respond, listening, voting, selecting language channels, chip card reading and displaying conference and user-related information. It is stylistically and functionally similar to the DCN-CONCS Delegate Unit with Channel Selector, but also includes a chip card reader and a graphic display with backlighting.

**Features**

- Low susceptible for mobile phones
- Compact, attractive delegate unit
- Built-in fold-away flat-panel loudspeaker
- Five voting buttons
- Cable connections located underneath the unit
- External present and fraud contact

Specifications

	Channel selector with channel number display with back lighting and channel select keys
	Headphone socket and volume control on each side of the unit
	Socket for external microphone or headset microphone
	Graphic LCD screen
	Five button with LED indicators (for use in combination with the graphic LCD screen). The soft-keys can provide users with display information such as messages, conference- and microphone user-related information. Depending on the application software the five soft-keys can be used as voting buttons with confirmation indicators (yellow LEDs)
	Identification and access control by card reader with or without PIN
Controls and indicators	Socket for pluggable condenser microphone (ordered separately) with built-in pop and windshield, complete with a light ring which illuminates when the microphone is on
	Built-in fold-away flat-panel loudspeaker
	Microphone on/off or request-to-speak button
	Two 'Microphone on' indicators
	'Request-to-speak' confirmation indicator (green LED)
	'VIP' confirmation indicator (yellow LED) 'VIP' LED is lit when the delegate unit is part of the notebook, which is available when PC control software is used
	'De-init' switch on the underside of the unit

Specifications continued on next page

DCN-CONFF Specifications continued from previous page

Specifications

Interconnection	6.5 ft. (2 m) cable terminated in a molded six-pole circular connector	
	Six-pole circular connector for loop-through connections	
	Eight-pole modular jack connector for Intercom Handset LBB 3555/00 and external present and Fraude contact e.g., a fingerprint reader	
	Left and right headphones sockets (3.5 mm (0.14 in) stereo jack type)	
Connection for external microphone or headset microphone (3.5 mm (0.14 in.) stereo jack type)		
Technical characteristics	Mounting	Tabletop (portable or fixed mounting) and flush mounting
	Dimensions (H x W x D)	Table top: 2.0 x 10.8 x 6.1 in. (50 x 275 x 155 mm)
		Flush mounted: 1.2 x 10.8 x 6.1 in. (30 x 275 x 155 mm)
	Weight	Approx. 3.3 lbs. (1.5 kg)
	Color	Charcoal base with silver panel

Specify Part Number
DCN-CONCM

DCN-NG Concentus Chairman

This stylish, low susceptible for mobile phones and ergonomically designed chairman unit is equipped with all the necessary facilities to enable the user to function as chairman of a conference. Similar in appearance to the DCN-CONFF

Delegate Unit, the DCN-CONCM Chairman Unit includes a microphone priority button.



Features

- Low susceptible for mobile phones
- Compact, attractive delegate unit
- Built-in fold-away flat-panel loudspeaker
- Five voting buttons
- Cable connections located underneath the unit
- External present and fraud contact

Specifications continued on next page

DCN-CONCM Specifications continued from previous page

Specifications

	Channel selector with channel number display with backlighting and channel select keys
	Headphone socket and volume control on each side of the unit
	Socket for external microphone or headset microphone
	Graphic LCD screen
	Five button with LED indicators (for use in combination with the graphic LCD screen). The soft-keys can provide users with display information such as messages, conference- and microphone user-related information. Depending on the application software the five soft-keys can be used as voting buttons with confirmation indicators (yellow LEDs).
Controls and indicators	Identification and access control by card reader with or without PIN
	Socket for pluggable condenser microphone (ordered separately) with built-in pop and windshield, complete with a light ring which illuminates when the microphone is on.
	Built-in fold-away flat-panel loudspeaker
	Microphone on/off or request-to-speak button
	Two 'Microphone on' indicators
	Priority key which causes an optional chime tone to sound while temporarily or permanently muting all active delegate units
	'De-init' switch on the underside of the unit
	6.5 ft. (2 m) cable terminated in a molded six-pole circular connector
	Six-pole circular connector for loop-through connections
Interconnection	Eight-pole modular jack connector for Intercom Handset LBB 3555/00 and external present and Fraude contact e.g., a fingerprint reader
	Left and right headphones sockets (3.5 mm (0.14 in) stereo jack type)
	Connection for external microphone or headset microphone (3.5 mm (0.14 in) stereo jack type)
	Mounting Tabletop (portable or fixed mounting) and flush mounting
Technical characteristics	Dimensions (H x W x D) Table top: 2.0 x 10.8 x 6.1 in. (50 x 275 x 155 mm) Flush mounted: 1.2 x 10.8 x 6.1 in. (30 x 275 x 155 mm)
	Weight Approx. 3.3 lbs. (1.5 kg)
	Color Charcoal base with silver panel

Accessories



DCN-MICS and DCN-MICL

The DCN-MICS and DCN-MICL are unidirectional microphones with an adjustable stem for use with DCN-IDESK-L Interpreter desk.